



CP-D80DW


REWIND FUNCTION - 2 PRINT SIZES / 1 MEDIA

The latest innovation by Mitsubishi Electric in digital sublimation printing. The **CP-D80DW**, also designed with space in mind, prints high resolution photographs in just 11.3 seconds with a 96% reduction in energy consumption in stand-by mode.

MAIN FEATURES

- 2 print sizes - 1 media
- Dust-free mechanism
- Energy saving
- Rewind function
- High resolution
- Compact design
- Matte / Glossy

FEATURES



MAIN FEATURES

• 2 print sizes - 1 media

The outstanding feature in the new CP-D80DW-S is the possibility to produce two print sizes (5x15cm (2x6") and 10x15cm (4x6")) from just one media paper saving time, reducing stock references and making maintenance and use easier.

• -96% Standby power saved

CP-D80DW-S is designed to reduce power consumption in sleep mode by up to 96%. Standby power refers to the electric power consumed by electronic appliances while they are switched off or in a standby mode.

• Rewind Function

New Rewind Function has been included in order to optimize the 10x15cm (4x6") prints. When the last half part of the ribbon patch is not used in the last order it can be capable for next printing order of 10x15cm (4x6"). This function cannot be used with Fine mode or Matte print. *10x15 (4x6") print speed 8.4sec in Fine mode without rewind function.

• High resolution

Mitsubishi Electric's printers incorporate the newly developed image processing methods making possible to reproduce smooth edges and natural images at 300DPI.

• Matte finishing


A matte finish is a highly textured print finish, similar to that of a satin finish. It is much duller and does not reflect light. Many photographers prefer to produce matte finishes due to market demands.

• Compact size

CP-D80DW-S is convenient for professionals who require Mitsubishi Electric's high quality in a small and compact design which fits seamlessly into any installation space.

• Dust-free system

The CP-D80DW-S is ideal for environments that suffer a higher level of pollution or dust. It has in-built separators that are designed to circulate the air more efficiently, keeping the heads separated from the power supply and reducing the level of contamination in the printing zone.





SPECIFICATIONS

Front panel

- 1 Paper strip bin
- 2 Power indicator
- 3 Paper ribbon indicator
- 4 Alarm indicator
- 5 Print outlet
- 6 Open button

Rear panel

- 1 Power switch
- 2 Power socket (AC line)
- 3 Fan cover Handle for transporting
- 4 USB terminal
- 5 Securing holes for the cable tie



TECHNICAL SPECIFICATIONS

Print deck	Single-deck																															
Printing Method	Dye Sublimation thermal transfer line 3-color face progressive printing (yellow, magenta, and cyan) and surface lamination																															
Gradations	256 (8-bit) for each color																															
Print resolution	300DPI																															
Photo finishing	Matte/Glossy																															
Media performance	<table border="1"> <thead> <tr> <th>Ref.</th> <th>Print Size</th> <th>Total prints</th> <th>Prints x Roll</th> <th>Print time*</th> </tr> </thead> <tbody> <tr> <td rowspan="4">D868</td> <td>5x15cm (2x6")</td> <td>860</td> <td>860 x 2</td> <td>8.3s</td> </tr> <tr> <td>10x15cm (4x6")</td> <td>430</td> <td>430 x 2</td> <td>11.3s</td> </tr> <tr> <td>15x15cm (6x6")</td> <td>215</td> <td>215 x 2</td> <td>18.2s</td> </tr> <tr> <td>15x20cm (6x8")</td> <td>215</td> <td>215 x 2</td> <td>21.5s</td> </tr> <tr> <td rowspan="2">D757</td> <td>13x13cm (5x5")</td> <td>230</td> <td>230 x 2</td> <td>16.2s</td> </tr> <tr> <td>13x18cm (5x7")</td> <td>230</td> <td>230 x 2</td> <td>19.3s</td> </tr> </tbody> </table>	Ref.	Print Size	Total prints	Prints x Roll	Print time*	D868	5x15cm (2x6")	860	860 x 2	8.3s	10x15cm (4x6")	430	430 x 2	11.3s	15x15cm (6x6")	215	215 x 2	18.2s	15x20cm (6x8")	215	215 x 2	21.5s	D757	13x13cm (5x5")	230	230 x 2	16.2s	13x18cm (5x7")	230	230 x 2	19.3s
Ref.	Print Size	Total prints	Prints x Roll	Print time*																												
D868	5x15cm (2x6")	860	860 x 2	8.3s																												
	10x15cm (4x6")	430	430 x 2	11.3s																												
	15x15cm (6x6")	215	215 x 2	18.2s																												
	15x20cm (6x8")	215	215 x 2	21.5s																												
D757	13x13cm (5x5")	230	230 x 2	16.2s																												
	13x18cm (5x7")	230	230 x 2	19.3s																												
Interface	Hi-Speed USB Ver.2.0																															
Memory size	64MB – Data transfer is possible during printing																															
Dimensions (W / D / H)	275/446/170mm (10.8/17.6/6.7")																															
Weight	12kg (26.5lb.)																															
Power supply	220-240VAC, 50/60Hz. / 120VAC, 50/60Hz.																															
Power consumption	2.4A (220-240VAC, 50/60Hz.) / 4.6A (120VAC, 50/60Hz.) / 0.05W (Standby mode)																															
Accessories	80DW:120V and 230V, 80DW-S:230V, Ink cassette (1), CD-ROM (1), Paper flange (1 set), Spacers (1 set), Quick setup guide (1), Paper strip bin (1), Cable tie (2), Securing band (1), Screw for securing band (1)																															
Compatibilities	PC/MAC / Kiosk gifts / Click																															

Mitsubishi Electric Europe CONTACTS

Mitsubishi Electric Europe B.V. German Branch
Mitsubishi Electric Europe B.V. Benelux Branch
Mitsubishi Electric Europe B.V. French Branch

URL: www.mitsubishi-vis.de
URL: www.mitsubishielectric.nl
URL: www.vis.mitsubishielectric.fr

Mitsubishi Electric Europe B.V. Spanish Branch
Mitsubishi Electric Europe B.V. Italian Branch
Mitsubishi Electric Europe B.V. Scandinavian Branch
Mitsubishi Electric Europe B.V. UK Branch

URL: www.mitsubishidigitalphoto.com
URL: www.mitsubishielectric.it/vis
URL: www.mitsubishielectric.se
URL: www.mitsubishielectric.co.uk/vis